


KS100

Security server cabinet lock

ASSA ABLOY









Product description

- Real-time communication to the access control system ensures easy management of access rights
- Designed for standard 25 mm x 150 mm server lock openings
- Ideal for collocation data centers with multiple companies requiring access
- For use on left or right hand doors
- Standard server cabinet "Swing-handle" design
- Simple to integrate because it works with your new or existing access control system
- Possibility to store up to 10 emergency cards (only used in case of disconnection from the hub)
- Powered by PoE or external power supply
- Input for Door Position Sensor
- LED for status visualisation
- Mechanical override possibility
- Easy to integrate and install with your new or existing access control system

Scope of delivery

- KS100
- Handle
- Mounting plate
- SFIC Cam
- Handling selector
- Cam (x3)
- Mounting screws
- DPS (Door Position Sensor Cable, 24VDC Cable)

Technical data -

	Approvals	CE; FCC Part 15
	Dimension	222 x 42 x 33.5 mm (HxWxD)
	Required power supply	48VDC Power over Ethernet (PoE) 802.3af compliant oder 24VDC Power Supply
	Wireless operating range	2.4 GHz, IEEE 802.15.4, using AES 128bit encryption
	Operating temperature range	-10°C to 50°C
	RFID Technologies (Based on reader type)	iCLASS™/ISO ISO1443B; iCLASS™ SEOS, iCLASS™ SE, MIFARE® classic, MIFARE® plus, DESFire® EV1, and NFC